

FlexStack Series



Key Parameters

Items	FS 12-210
Nominal Capacity (Ah)	210
	14.6V @ 0.2C to 10V
Min. Capacity (Ah)	205
	14.6V @ 0.2C to 10V
Charge Voltage (V)	14.6
Standard Charging Current (A)	105
Max. Continuous Charging Current (A)	170
Discharge Voltage (V)	10
Standard Discharge Current (A)	105
Max. Continuous Discharging Current (A)	170
Operating Temp. (°C)	0 ~ 55
	-20 ~ 60
Cycle Life	≥ 6000
	Charging / Discharging @ 0.2C 70% Capacity
Impedance (mohm)	< 50
Weight (kg)	~21.5
Protection Level	IP 67
Connection Mode	up to 6 in series connection
Dimension (L*D*H, mm)	462/211/270mm

FlexStack Series



Paramètres Clés

Articles	FS 12-210
Capacité Nominale (Ah)	210
	14.6V @ 0.2C to 10V
Capacité Min. (Ah)	205
	14.6V @ 0.2C to 10V
Tension de Charge (V)	14.6
Courant de Charge Standard (A)	105
Courant de Charge Continu Max. (A)	170
Tension de Décharge (V)	10
Courant de Décharge Standard (A)	105
Courant de Décharge Continu Max. (A)	170
Temp. de Fonctionnement (°C)	0 ~ 55
	-20 ~ 60
Durée de Vie (Cycles)	≥ 6000
	Charging / Discharging @ 0.2C 70% Capacity
Impedance (mohm)	< 50
Poids (kg)	~21.5
Niveau de Protection	IP 67
Mode de Connexion	up to 6 in series connection
Dimension (L*D*H, mm)	462/211/270mm