

FlexStack Series



Key Parameters

| Items | FS 12-210 |
|---|--|
| Nominal Capacity (Ah) | 210 |
| | 14.6V @ 0.2C to 10V |
| Min. Capacity (Ah) | 205 |
| | 14.6V @ 0.2C to 10V |
| Charge Voltage (V) | 14.6 |
| Standard Charging Current (A) | 105 |
| Max. Continuous Charging Current (A) | 170 |
| Discharge Voltage (V) | 9.2 |
| Standard Discharge Current (A) | 105 |
| Max. Continuous Discharging Current (A) | 170 |
| Operating Temp. (°C) | 0 ~ 55 |
| | -20 ~ 60 |
| Cycle Life | ≥ 6000 |
| | Charging / Discharging @ 0.2C 70% Capacity |
| Impedance (mohm) | < 50 |
| Weight (kg) | ~21.5 |
| Protection Level | IP 67 |
| Connection Mode | up to 6 in series connection |
| Dimension (L*D*H, mm) | 462/211/270mm |

FlexStack Series



Paramètres Clés

| Articles | FS 12-210 |
|--------------------------------------|--|
| Capacité Nominale (Ah) | 210 |
| | 14.6V @ 0.2C to 10V |
| Capacité Min. (Ah) | 205 |
| | 14.6V @ 0.2C to 10V |
| Tension de Charge (V) | 14.6 |
| Courant de Charge Standard (A) | 105 |
| Courant de Charge Continu Max. (A) | 170 |
| Tension de Décharge (V) | 9.2 |
| Courant de Décharge Standard (A) | 105 |
| Courant de Décharge Continu Max. (A) | 170 |
| Temp. de Fonctionnement (°C) | 0 ~ 55 |
| | -20 ~ 60 |
| Durée de Vie (Cycles) | ≥ 6000 |
| | Charging / Discharging @ 0.2C 70% Capacity |
| Impedance (mohm) | < 50 |
| Poids (kg) | ~21.5 |
| Niveau de Protection | IP 67 |
| Mode de Connexion | up to 6 in series connection |
| Dimension (L*D*H, mm) | 462/211/270mm |